



all dimensions in mm

Part number key

Modular	#####
Standard	#####
Calculated data	#####

Please see our customisation options page for details on the modifications available on our products. Advice and guidance on these options are available from your local sales contact.

Note: Brakes are not available on TEFC (Totally Enclosed Fan Cooled) motors.

Technical data

1 Part number		-	-	-	-	-	-
2 Minimum voltage available	V	12	24	24	24	24	24
3 Nominal power	W	50	75	95	125	150	190
4 Nominal speed	rpm	2000	2500	3000	4000	4000	6000
5 Nominal continuous torque (S1)	Nm	0.24	0.29	0.30	0.30	0.36	0.30
6 Input current 240 V AC	A	1.20	1.30	1.10	1.20	1.80	1.50
7 Input current 220 V AC	A	1.30	1.40	1.20	1.30	1.80	1.60
8 Approximate starting current	A	3 x full load	3 x full load	3 x full load	3 x full load	3 x full load	3 x full load
9 Input power	W	160	200	200	240	350	340

Thermal data

16 Ambient temperature	°C	40
------------------------	-----------	----

Mechanical data

17 Radial load [distance from flange]	N [mm]	200 [15]
---------------------------------------	---------------	----------

Other data

18 Weight	Kg	3.57
19 Enclosure		VENT/TENC
20 IP Rating - Ventilated		IP23
21 IP Rating - TENC [with terminal box]		IP50 [IP54]
22 Insulation Class		F
23 Type		Series wound
24 Direction		Reversible

Compatible products

Gearbox	+L mm	Brake	+L mm
M Box	85.0	0.4 Nm	35.0
MWS	110.0		
MIW	83.0		
L Box	108.0		
LWS	127.0		
LIW	102.0		
LIS	108.0		

Key
Standard combination
Modular combination

+L mm = approximate added length*

*additional length may also be required for mounting flange between components