

all dimensions in mm

Part number key

Modular	#####
Standard	#####
Calculated data	#####

Technical data


1 Part number		-	-	-	-	-	-	-
2 Gear ratio	:1	12.5	15	25	30	40	60	75
3 Stages		1	1	1	1	1	1	1
4 Max. continuous torque (S1) ¹	Nm	75.0	75.0	75.0	75.0	75.0	75.0	60.0
5 Max. intermittent torque	Nm	120.0	120.0	120.0	120.0	120.0	120.0	96.0
6 Efficiency	%	85	80	75	70	65	55	45
7 Backlash	arc.min	10-25	10-25	10-25	10-25	10-25	10-25	10-25
8 Max. axial load (dynamic)	N	600	600	600	600	600	600	600
9 Max. radial load, 12 mm from flange	N	800	800	800	800	800	800	800
10 Weight	Kg	3.4	3.4	3.4	3.4	3.4	3.4	3.4
11 Gear material		Bronze						

¹ S1 duty cycle based on 3000 RPM input speed

Compatible products

BLDC	+L mm	PMDC	+L mm	AC	+L mm
PBL86-55	111	BRx90-50	153	SD13	152
PBL86-80	136	BRx90-75	183	SD18	158
		PM90-150	153	SD48	170
		PM90-180	183		
		EPM63-50	150		
		EPM63-50 (V)	163		
		EPM63-75	175		
		EPM63-75 (V)	188		
		EPM63-100	200		
		EPM63-100 (V)	213		

Gearbox output position



Compatible products key

Product name	Standard combination
Product name	Modular combination

(V) = ventilated
+L mm = approximate added length*

*additional length may also be required for mounting flange between components