



all dimensions in mm

Part number key

Modular	#####
Standard	#####
Calculated data	#####

Please see our customisation options page for details on the modifications available on our products. Advice and guidance on these options are available from your local sales contact.

Note: Brakes are not available on TEFC (Totally Enclosed Fan Cooled) motors.

Technical data

1 Part number		-	-	-	-	-	-	-	-
2 Phases		1	1	1	1	3	3	3	3
3 Frequency	Hz	50	50	60	60	50	50	60	60
4 Nominal voltage	V AC	230	230	115	115	400	400	230	230
5 Nominal power	W	150	190	55	100	190	250	190	250
6 Nominal speed	rpm	1400	2800	1700	3400	1400	2800	1700	3400
7 Nominal continuous torque (S1)	Nm	1.00	0.65	0.84	0.53	1.30	0.85	1.07	0.70
8 Nominal continuous current (S1)	A	1.70	1.70	-	-	0.50	0.75	-	-
9 Starting Current	A	4.25	4.25	0	0	1.25	1.88	0	0
10 Input Watts	W	308	324	308	324	300	400	300	400
11 Capacitor Value	M.F.D	40/50	40/50	40/50	40/50	-	-	-	-
12 Starting Torque Full Load	%	150	130	150	130	150	150	150	150
13 Stack length	mm	56	56	56	56	56	56	56	56
14 Number of poles		4	2	4	2	4	2	4	2
15 Rotor inertia	Kg/cm ²	-	-	-	-	-	-	-	-

Thermal data

16 Ambient temperature	°C	40
------------------------	----	----

Mechanical data

17 Radial load [distance from flange]	N [mm]	200 [15]
---------------------------------------	--------	----------

Other data

18 Weight	Kg	6.5
19 Enclosure		VENT/TEFC
20 IP Rating - Ventilated		IP20
21 IP Rating - TE/TEFC		IP54
22 Insulation Class		F
23 Type		Capacitor start, asynchronous
24 Direction		Reversible

Compatible products

Gearbox	+L mm	Brake	+L mm
M Box	85	0.4 Nm	35
MWS	110		
MIW	83		
L Box	108		
LWS	127		
LIW	102		
LIS	108		
GB9	138		
GB12	110		
GB65	150		

+L mm = approximate added length*

Compatible products key

Product name	Standard combination
Product name	Modular combination

*additional length may also be required for mounting flange between components